



## Instructions for Continued Airworthiness

### **FAA-STC SA5460SW**

# Beechcraft King Air C90 Aircraft With P&W PT6A-21 Engines In Place of P&W PT6A-20A Engines

**REV. IR**

NOTICE

This document must be referenced on Block 8 of FAA form 337 and added to the aircraft permanent record as required by 14 CFR Part 91, §91.417(a)(2)(vi) when the reference FAA-STC modification is accomplished on eligible aircraft. This document complies with the requirements of 14 CFR Part 23, §23.1529, in accordance with 14 CFR Part 23, Appendix G.

Aircraft Serial No. \_\_\_\_\_

Aircraft Registration No. \_\_\_\_\_



FAA-STC SA5460SW  
Beechcraft King Air C90 Aircraft with P&W PT6A-21 engines  
In Place of PT6A-20A Engines  
**Instructions For Continued Airworthiness**

---

**LOG OF REVISIONS**

Rev No.	Revision Date	Review	Affected Pages	Description of Revision
IR	Feb 22 2005	<i>Carly E. Hill</i>	All	Initial Release



FAA-STC SA5460SW  
Beechcraft King Air C90 Aircraft with P&W PT6A-21 engines  
In Place of PT6A-20A Engines  
**Instructions For Continued Airworthiness**

---

**Table of Contents:**

1.	Introduction: .....	4
2.	Description:.....	4
3.	Special procedures: .....	4
4.	Servicing information: .....	4
5.	Maintenance Instructions: .....	4
6.	Troubleshooting: .....	5
7.	Removal and Replacement:.....	5
8.	Diagrams: .....	5
9.	Special Inspection Requirements: .....	5
10.	Application of Special Treatments: .....	6
11.	Data: .....	6
12.	Special Tools: .....	6
13.	Additional Information For Commuter Category Aircraft: .....	6
14.	Recommended Overhaul Period:.....	6
15.	Airworthiness Limitations: .....	7
16.	Revision: .....	9
17.	Assistance: .....	9



FAA-STC SA5460SW  
Beechcraft King Air C90 Aircraft with P&W PT6A-21 engines  
In Place of PT6A-20A Engines  
**Instructions For Continued Airworthiness**

---

**1. INTRODUCTION:**

This document provides instructions for the continued airworthiness (ICA) for Blackhawk Modifications, Inc. FAA-STC SA5460SW to install two Pratt & Whitney (P&W) PT6A-21 engines and any of the following propellers listed in Section 2 on Beechcraft King Air C90 aircraft that were originally equipped with P&W PT6A-20A engines.

**NOTICE:**

Section 15, titled "Airworthiness Limitations" is FAA approved and specifies maintenance required under 43.16 and 91.403 of the Federal Aviation Regulations unless an alternative program has been FAA approved. To remain in compliance with the STC, the aircraft shall be maintained in accordance with these limitations.

This document supplements or supersedes any Beechcraft Aircraft King Air 90 Series Maintenance Manual, only in those areas listed herein for the appropriate aircraft model and serial number.

**2. DESCRIPTION:**

This STC installs two Pratt & Whitney PT6A-21 engines on Beechcraft King Air C90 aircraft that were originally equipped with P&W PT6A-20A engines. The following propeller may be reinstalled or newly installed.

Propeller	Min./Nominal Diameter (in.)
HARTZELL 3-BLADED MODEL NO. HC-B3TN-3( ,B,M)/T10173(E,B,NB)-8	90-3/8" / 93 3/8"

**3. SPECIAL PROCEDURES:**

None

**4. SERVICING INFORMATION:**

Service PT6A-21 engines in accordance with appropriate Raytheon Aircraft Beech King Air Model 90 Series Maintenance Manual for the aircraft serial number being serviced and appropriate Pratt & Whitney Maintenance Manual.



FAA-STC SA5460SW  
Beechcraft King Air C90 Aircraft with P&W PT6A-21 engines  
In Place of PT6A-20A Engines  
**Instructions For Continued Airworthiness**

---

**5. MAINTENANCE INSTRUCTIONS:**

Maintain PT6A-21 engines in accordance with appropriate Raytheon Aircraft Beech King Air Model 90 Series Maintenance Manual for the aircraft serial number being serviced and appropriate Pratt & Whitney Maintenance Manual.

**6. TROUBLESHOOTING:**

Troubleshooting guidance may be found in the documents listed in section 5. Otherwise, contact Blackhawk Modifications, Inc. for assistance.

**Blackhawk Modifications, Inc.**  
1800 E. Sahara Dr.  
Las Vegas NV 85108

**7. REMOVAL AND REPLACEMENT:**

Removal of new parts is the opposite of installation detailed in Blackhawk Installation drawing 003-01, Rev. B, dated 02/22/05 or later FAA approved revision. For replacement

- Standard AN, MS, AE Parts listed with the installation can be obtained from appropriate and suitable vendor.
- Beechcraft parts listed with the installation can be obtained from Beechcraft.
- All other parts required for replacement should be fabricated per installation drawing listed using appropriate material as called out in material specification provided in list of materials. If you have any questions, contact

**Blackhawk Modifications, Inc.**  
1800 E. Sahara Dr.  
Las Vegas, NV 85108

**8. DIAGRAMS:**

Installation Dwg No. 03-001, titled "Installation Engine, PT6A-21 Beech C90"

**9. SPECIAL INSPECTION REQUIREMENTS:**



FAA-STC SA5460SW  
Beechcraft King Air C90 Aircraft with P&W PT6A-21 engines  
In Place of PT6A-20A Engines  
**Instructions For Continued Airworthiness**

---

Conduct routine inspections on the PT6A-21 engines in accordance with appropriate Raytheon Aircraft Beech King Air Model 90 Series Maintenance Manual for Serial Number being serviced and per appropriate PT6A Pratt & Whitney Maintenance Manual.

**10. APPLICATION OF SPECIAL TREATMENTS:**

None

**11. DATA:**

Installation Dwg No. 03-001, titled "Installation Engine, PT6A-21 Beech C90"

**12. SPECIAL TOOLS:**

Per appropriate Raytheon Aircraft Beech King Air Model 90 Series Maintenance Manual for Serial Number being serviced and per appropriate PT6A Pratt & Whitney Maintenance Manual.

**13. ADDITIONAL INFORMATION FOR COMMUTER CATEGORY AIRCRAFT:**

Not Applicable

**14. RECOMMENDED OVERHAUL PERIOD:**

Per appropriate Raytheon Aircraft Beech King Air Model 90 Series Maintenance Manual for Serial Number being serviced and per appropriate PT6A Pratt & Whitney Maintenance Manual.



FAA-STC SA5460SW  
Beechcraft King Air C90 Aircraft with P&W PT6A-21 engines  
In Place of PT6A-20A Engines  
**Instructions For Continued Airworthiness**

---

**15. AIRWORTHINESS LIMITATIONS:**

**NOTICE:**

This section is FAA approved and specifies maintenance required under 43.16 and 91.403 of the Federal Aviation Regulations unless an alternative program has been FAA approved. To remain in compliance with the STC, the aircraft shall be maintained in accordance with these limitations.

**INSTRUMENT MARKINGS**

Interstage Turbine Temperature (ITT)

Dashed Red-Line (Radial) ..... 1090°C (Starting)  
Solid Red-Line (Radial)..... 695°C  
Normal Operating Range (Green-Arc)..... 400°C to 695°C

Oil Pressure

Red-Line (Radial) Maximum ..... 100 psi  
Normal Operating Range (Green-Arc)..... 80 to 100 psi  
Red-Line (Radial) Minimum ..... 40 psi

**CENTER OF GRAVITY LIMITS (LANDING GEAR EXTENDED)**

Aft Limit..... 160.0 inches aft of datum at all weights



FAA-STC SA5460SW  
 Beechcraft King Air C90 Aircraft with P&W PT6A-21 engines  
 In Place of PT6A-20A Engines  
**Instructions For Continued Airworthiness**

**15. AIRWORTHINESS LIMITATIONS (CONTINUED):**

**ENGINE OPERATING LIMITS**

The following limitations are to be observed in the operation of this airplane equipped with two Pratt and Whitney PT6A-21 engines. Each column is a separate limitation. The limits presented do not necessarily occur simultaneously.

POWER SETTING	SHP	TORQUE FT. LB. (1)	ITT °C	GAS GEN RPM % N <sub>1</sub> (9)	PROP RPM N <sub>2</sub>	OIL PRESS PSIG (2)	OIL TEMP °C (3)
Start	-	-	1090 (4)	-	-	-	-40 (min)
Low Idle	-	-	660 (5)	51 (min)	-	40 (min)	-40 to 99
High Idle	-	-	-	70 (approx)	-	-	0 to 99
Takeoff and Max Continuous	550	1315	695	101.5	2200	80 to 100	10 to 99
Cruise Climb and Max Cruise	495 (10)	1315 (6)	695	101.5	2200	80 to 100	10 to 99
Max Reverse (7)	-	-	695	88	2100	80 to 100	0 to 99
Transient (Acceleration)	-	1500 (4)	825 (4)(8)	102.6	2420	-	0 to 99

- (1) Maximum permissible sustained torque is 1315 ft-lbs. Propeller speeds (N<sub>2</sub>) must be set so as not to exceed power limitation.
- (2) When gas generator speeds are above 72%N<sub>1</sub> and oil temperatures are between 60°C and 70°C, normal oil pressure is between 80 and 100 psi. Oil pressure between 40 and 80 psi is undesirable; it should be tolerated only for completion of the flight, and then only at a reduce power setting. Oil pressure below 40 psi is unsafe; it requires that either the engine be shut down, or that a landing be made at the nearest suitable airport, using the minimum power require to sustain flight.
- (3) For increased service life of engine oil, and oil temperature of between 74 °C and 80°C is recommended. A minimum oil temperature of 55°C is recommended for fuel heater operation at takeoff temperature
- (4) These values are time limited to two seconds.
- (5) High ITT at ground idle may be corrected by reducing accessory load and/or increasing N<sub>1</sub> RPM
- (6) Cruise torque values vary with altitude, temperature, and RPM.
- (7) If installed, reverse power operation is limited to one minute.
- (8) High generator loads at low N<sub>1</sub> speeds may cause the ITT transient temperature limit to be exceeded. Observe generator load limits provided in SECTION IV LIMITATIONS of the basic AFM.
- (9) For every 10°C below -30°C OAT, reduce maximum allowable N<sub>1</sub> by 2.2%.
- (10) Observe Torque and RPM indications provided in basic AFM performance sections.





FAA-STC SA5460SW  
Beechcraft King Air C90 Aircraft with P&W PT6A-21 engines  
In Place of PT6A-20A Engines  
**Instructions For Continued Airworthiness**

---

**16. REVISION:**

Each time this ICA is revised or reissued, the revised ICA will be distributed to operators using a Service Letter/Bulletin by Blackhawk Modifications. This revision will include a new Log of Revisions page along with the revised pages. The lower right hand corner of each revised page will reflect the revision letter. That portion of text or an illustration, which has been revised by the addition of, or change in, information is denoted by a solid revision bar located adjacent to the area of change, and placed along the outside margin of a page. Revision bars show only information changed within latest revision.

**17. ASSISTANCE:**

For assistance with ICA issues not addressed herein, contact Blackhawk Modifications, Inc. at the following address or phone number.

**Blackhawk Modifications, Inc.**  
1800 E. Sahara Dr.  
Las Vegas, NV 85108  
(831) 624-6996